

**GRES PORCELLANATO  
IMPASTO COLORATO**

COLOURED BODY  
PORCELAIN STONEWARE












DURCHGEFÄRBTES  
FEINSTEINZEUG

КЕРАМОГРАНИТ,  
ОКРАШЕННЫЙ В МАССЕ

**DIGITAL TECHNOLOGY**

GRÈS CÉRAME COLORÉ  
DANS LA MASSE

PORCELÁNICO DE PASTA  
DE COLOR

<b>Dati tecnici secondo norme:                      Technical data conform to:                      Caractéristiques techniques d'après normes:                      Technische Daten nach den Normen:                      EN 14411 Bia GL</b>			<b>KADO</b>	<b>KADO OUT</b>
	<b>Caratteristiche Tecniche                      Technical Data                      Caractéristiques Techniques                      Technische Daten</b>	<b>Norme                      Normes                      Normes                      Norm</b>	<b>Valori                      Value                      Valeur                      Wert</b>	<b>Valori                      Value                      Valeur                      Wert</b>
	Resistenza all'abrasione Abrasion resistance Résistance à l'abrasion Abrasionswiderstandigkeit	ISO 10545 - 7	PEI IV	PEI IV
	Assorbimento d'acqua Water absorption Absorption d'eau Wasseraufnahme	ISO 10545 - 3	≤ 0,5%	≤ 0,5%
	Resistenza alla flessione Breaking modulus Résistance à la flexion Biegefestigkeit	ISO 10545 - 4	≥ 35 N/mm <sup>2</sup>	≥ 35 N/mm <sup>2</sup>
	Resistenza al gelo Resistance to frost Résistance au gel Frostbeständigkeit	ISO 10545 - 12	NON GELIVE FROST PROOF INGÉLIF FROSTSICHER	NON GELIVE FROST PROOF INGÉLIF FROSTSICHER
	Resistenza all'attacco acido e basico Glaze resistance to acid and alkaline attack Résistance aux acides et aux bases Säure-und laugenfestigkeit	ISO 10545 - 13	RESISTE RESISTS RESISTE BESTÄNDIG	RESISTE RESISTS RESISTE BESTÄNDIG
	Durezza Mohs Mohs hardness Dureté Mohs Haerte Mohs	EN101	5	-
	Resistenza alle macchie Stain resistance Résistance aux taches Fleckenfestigkeit	ISO 10545 - 14	TOTALE COMPLETE TOTALE ABSOLUT	TOTALE COMPLETE TOTALE ABSOLUT
	Scivolosità Slipperiness Degré de glissement Rutschhemmung	DIN 51130	R10	R11
	Resistenza allo scivolamento Slip resistance Résistance au glissement Rutschhemmung	DIN 51097	B	C
	Scivolosità Coefficient of friction Degré de glissement Rutschhemmung	ANSI A137-1	≥ 0,42	≥ 0,42
	Stonalizzazione Shading Denuançage Spielfarbig	-	V2	V2

I valori indicati nella tabella si riferiscono alle prove eseguite sul colore ICE.

The values in the table refer to the tests performed on color ICE.

Les valeurs indiquées dans le tableau se réfèrent aux essais exécutés sur le couleur ICE.

Die in der Tabelle angegebenen Werte beziehen sich auf die Tests die auf dem Farbe ICE ausgeführt wurden.

Los valores indicados en la tabla se refieren a las pruebas realizadas sobre el color ICE.

Указанные в таблице значения относятся к испытаниям, проведенным на бежевом оттенке ICE.